

946C25- C25 Cabin Camera 1080P,2.8mm,IR, audio,PON connector.



1920*1080@30fps Resolution

Ultra capacitor ensures power-off Protection

Support POE(DC48V) or PON(DC12V) power input interface

With infrared Led light -- 5-8 meters of infrared consumption range

Multiple optional Lens;-support 2.8mm 4mm 6mm 8mm

Excellent low light effect, support 1080P 16:9 sensor

Top waterproof class-IP65

Application scenario Horizontally and Hoisting Installed

Support three kinds of stream

Support N9M protocol.

Specification	
Product Model	946C25
Sensor	946C24
Resolution	1/2.8"2MP"CMOS
Minimum Illumination	1920(H)x1080(V)
Electronic Shutter	0.05Lux (Color) ,0Lux(Infrared)
Back-Light Compensation	1/30 Second-1/10000 Second
S/N	Support
Infrared Range IR	5~8m
Lens	2.8mm,4mm,6mm,8mm M12, Fixed Aperture F1.8
FOV	2.8mm=H*V 104°55° 2.8mm=H*V 98° *54°
	4mm= H*V 89° 46°
	6mm= H*V 54° 29°
	8mm= H*V 41° 23°
Video Compression Standard	Default H.264 Support H.265
Compression Output Rate	512Kbps-8Mbps
Image Resolution	Main Stream:1080P(or 720p) @ 30fps
	Sub Stream VGA/D1/CIF @ 10FPS Default VGA 10FPS
	Net Transmission Stream: Default VGA 10FPS
CBR/VBR	Support Default VBR
Audio Compression Standard	G.711A 、 G.711U 、 ADPCM 、 G.726 默认 G711A
Network Port	10M/100M Adjustable Ethernet port
Audio Input	Build-in Audio Capture

Audio Capture Range	Maximum 5m
Network Protocol	TCP/IP、HTTP、DHCP、NTP、FTP、ONVIF
N9M	Support
Client Preview	Built-in WEB Server、Support IE Browser
Installation	Horizontally and Hoisting Installed
Operation Temperature	-40℃ ~ +70℃
Operation Humidity	0% - 90%
Power Supply	PON (DC9-16V) / POE(DC37-58V)
Waterproof Class	IP65(With Audio)
Power Consumption	PON<2w (Day Time) <3.5w (Night) ;
	POE<3w (Day Time) <4.5w (Night)
Dimension(Unit in mm)	101.5MM(L)x96MM(W)x52.6MM(H)
Dimension(Unit in mm)	

