

TX02-Z03H


Smart Zigbee Gateway



Online Real-time
Communication



Compact
Design



Multi-device
Management



OTA Upgrade

Compatible with

 **ZKBio CVSecurity**


Features



Online Real-time Communication
Remotely control the devices and monitor their status in real-time



Compact Design
Compact size for space-saving and flexible installation



Multi-device Management
Connect up to 6 wireless locks using the Zigbee 3.0 technology



OTA Upgrade
Support the OTA firmware upgrades for easier maintenance

Specifications

Technical	Supported Products	SL03-T420H
	Max. Sub-device Quantity	6
	Wireless Communication	Wi-Fi (IEEE 802.11b/g/n) @ 2.4 GHz Zigbee 3.0 (IEEE 802.15.4)
	Wireless Security	WPA-PSK / WPA2-PSK
	Hardware Interface	2 * 10 / 100Mbps RJ45 Port (WAN+LAN) Micro-USB Power Port
	Power Supply	DC 5V/1A
	Net Weight	0.15 kg
General	Gross Weight	0.23 kg
	Product Dimensions (L×W×H)	89.6 × 89.6 × 22.0 mm
	Package Dimensions (L×W×H)	145.0 × 130.0 × 55.0 mm
	Operating Temperature	-10°C to 55°C (14°F to 131°F)
	Operating Humidity	10% to 90% RH (Non-condensing)
	Certifications	CE
Package Contents	Device, 5V Power Adapter, USB Cable (USB-A to Micro-B), Ethernet Cable	

